

IsleSat

Serving Shetland, Fair Isle
and Orkney

Installation, Sales &
Service

Tel : 01950 422412

Technomate 5400CI + USB + PVR Ready



FTA + 10,000 Channels + USB 2.0 with: PVR Ready for Record & Playback of Channels, Music/JPEG & Software/Channel List Download + Component (YPbPr) Output + Blind Search + Sensitive Tuner + Optical SPDIF Digital Audio + USALS/DiSEqC 1.2. 1 Slot & 1 Card Reader. USB patches for multi-viewing.

One of the fastest receivers ever!

Specification

- Fully DVB compliant
- 10,000 TV & Radio Channels
- USB2.0 PVR Ready via powered external HDD or USB Flash Drive (memory stick) for Record & Playback functions
- Music player and JPEG viewer via powered external HDD or USB Flash Drive (memory stick)
- Fast Software & Channel List download via USB 2.0
- Component (YPbPr) Output
- Fast Blind Search (power scan)
- Super Sensitive tuner for very weak signals
- Optical Digital Audio S/PDIF Output
- Free to Air (FTA)
- Less than 1 Second channel change
- DiSEqC 1.0, 1.1, 1.2 & 1.3 (USALS) compatible
- DiSEqC Indicator
- Enhanced 16 Favourite Channel Groups and sort function
- Auto Navigation system – select as many satellites as you want to search automatically
- High quality video and audio by MPEG-2 standard
- Extended EPG and program reservation on EPG
- Easy-to-use menu system with comments for guidance
- Channel delete, move, rename and sort functions
- Automatic digital Satellite signal detecting Function
- Multiple switch types, LNB types and NTSC/PAL Monitor types
- Manual Transponder Editing
- Supports PAL/NTSC systems
- Parental Control function
- Last channel auto-saving and recall function
- Hi-speed software upgrade through RS-232(NULL Modem)
- Receiver-to-receiver data transfer via RS232
- PLL type RF-Modulator (Ch. 21- 69) and UHF tuning function
- Antenna-positioning-help function
- Various Games
- 9 Multipicture display
- Timer Function
- Multi-Event Timer
- Teletext Function
- Automatic FEC and PID detection and manual entry of PID value
- Pause function
- Loop through tuner and satellite
- Real Time Clock
- Multi-Language OSD
- Teletext & Subtitle Support by OSD and VBI
- LNB Short Circuit protection onboard
- 280mm x 55mm x 235mm